



CHAIN LUBE 1000

广州孚润 400-992-6811

TECHNICAL DATA AND TYPICAL CHARACTERISTICS



Appearance	Liquid
Odor	Mild petroleum
Color	Black
Specific gravity	.81
Viscosity	Light Penetrating Liquid
Flash point (T.C.C.)	110°F
% Non-volatile	20
% Volatile	80
Pour Point	Less than - 40°F
Low temperature range	- 20°F
Peak temperature range	750°F
Initial Boiling Point	More than 300°F
Weight	6.8 Lbs/Gal.
Coverage	Approx. 800 Sq Ft./Gal.
Surface Tension	27 dynes/cm @ 70°F
Electrical Conductivity	N/A
Solvent KB Value	37
Corrosion Protection ASTM (D-1748)	Excellent

FEATURES

ECONOMICAL

NON-SETTLING MoS2

HIGH PEAK TEMPERATURE RANGE

CONTAINS CORROSION INHIBITORS

BENEFITS

COSTS LESS THAN MOST LUBRICATING OILS.

WORKS IN ALL CENTRAL LUBRICATING EQUIPMENT

IDEAL FOR OVENS, KILNS & OTHER AREAS WITH ABOVE NORMAL OPERATING TEMPERATURES

PREVENTS RUST ON METAL AND PROVIDES EXCELLENT ACID FUM PROTECTION

<u>PACKAGE</u>	<u>PRODUCT #</u>	<u>CASE PACK</u>	<u>SHIPPING WEIGHT</u>
5 gal. pail	DSL305	1	40 lbs
16 gal. drum	DSL315	1	125 lbs
55 gal. drum	DSL355	1	415 lbs

Sold by Dri-Slide North America – 1452 Delashmut Avenue – Columbus, Ohio 43212

Website: www.russack.com Tel. #1-800-231-6901 Fax #1-800-600-0855 or (614)291-6929